



# Big capacity water baths “Precisbig”



DIGITAL CONTROL AND DISPLAY OF TEMPERATURE AND TIME.

ADJUSTABLE TEMPERATURE RANGE FROM AMBIENT +5 °C TO 99,9 °C. STABILITY: ±0,2 °C. HOMOGENEITY ±2 °C.

**SAFETY:** DIN 12877 STANDARD. THE UNIT WILL CUT OUT IF THERE IS INSUFFICIENT LIQUID OR IF THE BATH TEMPERATURE EXCEEDS THE SET TEMPERATURE. A MANUAL RESET ADJUSTABLE TEMPERATURE SAFETY THERMOSTAT IS PLACED AT THE BACK OF THE UNIT.

*Programmable temperature and time. Interior and exterior made from Stainless steel*

## FEATURES

Double skinned tank of AISI 304 stainless steel with an external case of AISI 304 stainless steel.

Heating elements embedded in INCOLOY|heat and corrosion resistant stainless steel.

## CONTROL PANEL

See page 89.

## MODELS

Part No.	Temperature maximum °C	Capacity litres	Height / Widht / Depth (usable) cm	Height / Widht / Depth (exterior) cm	Power W	Weight Kg
<b>6001240**</b>	99,9	160	40 80 50	96 100 70	9000	130
<b>6001241**</b>	99,9	220	40 110 50	96 140 70	9000	160

All baths with heating shelf and drainage. Faucet included.

Due to their power consumption are manufactured for three phase 380 V. 4 wheels and gable lids included.

## ACCESORIES

**Gable lid** for bath 6001240. Part No. **6000715**

**Gable lid** for bath 6001241. Part No. **6000716**

**Silicone oil** 4 liters. Temperature up to 300 °C. Viscosity 50 mm<sup>2</sup>/s at 25 °C. Melting point 318 °C. Part No. **1000027**

