



# Automatic bag sealer with printer "Seal-Com 3"

ACCORDING DIN 58953 SECTION 7 STANDARD. FOR SEALING STERILE PAPER, POLYPROPYLENE-POLYESTER BAGS. SPECIAL FOR A LARGE AMOUNT OF BAGS SEALING.

**NEW**

## FEATURES

Exterior made from AISI 304 stainless steel, ideal for sealing plastic paper bags, solid plastic paper and only paper bags.

Heating time: 4 minutes.

Seal width: 12 mm.

Sealing speed: 10 m/min.

Acoustic sign of cycle starting.

Temperature touch control from 60 to 220°C.

## CONTROL PANEL

LCD touch screen 7" indicating:

- Setpoint temperature and actual temperature.
- Date and time (automatic date change).
- Print size.

## PRINTING

Print sterilization date, expiration date, sterilization lot, name of the operator, name of the item and department.

MFG: 20190516LOT: 000000230OPERATOR: 00000000  
EXP: 20220206NO. /SECOND: /PACKAGED GOODS: DEPARTMENT: CE

## MODEL

Part No.	Height / Width / Depth (sealer) cm	Power W	Weight Kg
<b>4100049</b>	22 56 26	500	20



## ACCESSORIES

### Roller table

Measures cm: 74.5 width x 28.6 depth x 5.2 height.

Part No. **4100053**



## SEALING MACHINE ACCESSORIES

### Rolls of paper for sterilization "Polisteril"

Paper base polypropylene and polyester bags showing differing ink prints of sterilized items.

Part No.	Bag width cm	Bag length m
<b>4100075</b>	7,5	100
<b>4100100</b>	10	100
<b>4100200</b>	20	100



### Sterile paper "Policort" trimmer

Completely made of metal with back and reel support, for a capacity of 2 x 200mm or 4 x 100 mm wide reels.

Circular cutting knife edge.

Measurements: 13 high x 51 wide x 32 cm deep.

Weight: 2.8 Kg.

Part No. **4100045**



### Date stamping machine for sterile bags.

Part No. **4100046**

STERILIZED  
30 OCTOBER 2022  
VALID FOR 3 MONTHS.



**OPTIONS:** Ultrasonic cleaning baths for dentistry, "Ultrasons-Digit" (see page 94). Dry sterilizer "DRYTIME" poupinel oven (see page 136).

## ACCESSORIES FOR AUTOCAVES

### Mercury-free thermometer for recording autoclave's temperature.

It indicates the highest temperature reached by the autoclave to verify its correct operation.

AISI 304 stainless steel made body and glass lens resistant to humidity, pressure and high temperatures.

Range: -20/150°C. Accuracy: ± 2°C.

Part number **1097101** Without calibration.

Part number **1097102** With individual calibration report at 121°C.

